

Author Esa Kalistaja
Date 2020-05-15



1 Release type

Product/solution	UULA 2.2.1	
Release type	Demo	☐
	Proto	☐
	New product	☐
	Additional features /functionalities	☐
	SW product	☒
	Document update	☐
	Correction revision	☐
	Other [state here what]	☐

2 Release components

Release component	Name and version	
HW + version		
SW name + version	UULA 2.2.1	
Camera firmware		

Documentation	Name and version	
User manual	UULA user manual 2.2.1 After installation it is recommended to use User manual html version which can be found from header Help	☒
Installation guide	Setup program with a readme file	☒
Release note	Release Note UULA 2.2.1	☒

Recommended configuration is	
Uula SW	2.2.1
Camera FW	LCI 401, LCI1200, LCI1201 and LCI 1600: 4.9.1
	LCI1220 and LCI1620: 1.3.1
Motor FW (XY)	290319020
Height FW (RZ)	60818010

If your camera FW or UULA motor or height FW are not up-to-date, LMI Support is happy to update those. Please submit a technical support request through <https://support.lmi3d.com> (recommended) or by email at support@lmi3d.com.

Released SW version also requires that the calibration files are saved on the sensor, LMI support can help in this too if needed.

3 UULA 2.2.1 release features

UULA 2.2.1 makes it possible, if needed, to move the table manually in Y-direction at calibration phase. In addition, calibration with manual Z-move (U-XY) has been made easier.

4 UULA 2.2.0 release features

Uula support for sensor LCI1220 and LCI1620

FocalSpec Map not included in installer.

- Focalspec Map / Mountains Map software is recommended analysis tools for Uula scanner. Uula 2.2.0 installation package does not include before mentioned programs, but those need to be installed separately. Map installers are available on support pages.
- Updating Uula SW does not require reinstalling Map SW.

Intensity calibration

- User can use any sample for the intensity calibration and intensity compensation is done real-time.

Multiple layers displayed in Camera Preview window.

- Surface selection by top, bottom or brightest.

Simplified peak detection configuration based on material type

- Available material types are Opaque, Mirror and Transparent.

Advanced camera parameters

- Average Z
- Average Intensity
- Median Z
- Median Intensity
- Fill Gap Max
- Trim Edges
- Noise Removal X and Y
- Clustering Distance X and Z
- Minimum Length for Cluster
- Missing First Layer Distance
- Missing First Layer X Distance
- Missing First Layer Min Length
- Intensity Calibration (supported only by UULA with motor Z-move)
- Surface Mode
- Layer Sorting Order
- Effective Refractive Index
- Max Thickness
- Intensity Type

Height coloring with intensity in Pcd Viewer.

5 Known issues and problems

Known issues and problems

Old recipes, which are using Half Step Scan, need to be saved with Uula 2.2.0 before they are used for scanning.

If you have LCI1600 or LCI1620, add a paper (such as a Post-it Note) to hide the left side of the groove specimen, see user manual 2.3.2 Calibrating UULA.

Parameters of old Recipes with Jobs are advised to be checked before scanning. If parameters are not right, it is recommended to recreate the Jobs from the start.

6 Additional information

If there are any questions, please contact LMI by submitting a technical support request through <https://support.lmi3d.com> (recommended) or by email at support@lmi3d.com.

7 Disclaimer

Copyright

Copyright © 2020 by LMI Technologies, Inc. All rights reserved.

Proprietary

This document, submitted in confidence, contains proprietary information which shall not be reproduced or transferred to other documents or disclosed to others or used for manufacturing or any other purpose without prior written permission of LMI Technologies Inc.

No part of this publication may be copied, photocopied, reproduced, transmitted, transcribed, or reduced to any electronic medium or machine-readable form without prior written consent of LMI Technologies, Inc.

Trademarks and Restrictions

FocalSpec™ is a registered trademark of LMI Technologies, Inc. Any other company or product names mentioned herein may be trademarks of their respective owners.

Information contained within this manual is subject to change.

Contact Information

LMI Technologies, Inc.

9200 Glenlyon Parkway

Burnaby BC V5J 5J8

Canada

Telephone: +1 604-636-1011

Fax: +1 604-516-8368 www.lmi3d.com